

KR600 Series



KR600-E/M



KR601-E/M



KR602-E/M

RFID S50/S70 IC Card (13.56 MHz) Readers

Read Range

KRxxx-E: Up to 10CM

KRxxx-M: Up to 5CM

Reading Time

≤300ms

Input Port

External LED Control

External Buzzer Control

Material

ABS+PC with texture

Output Format

KRxxx-E: 26bit Wiegand (Default)

KRxxx-M: 34bit Wiegand (Default)

Power/Current

DC 6-14V / Max.70mA

LED

Red and Green LEDs

Operating Temperature

-20°C to 65°C(-10° to +70°C)

Operating Humidity

10% to 90% relative humidity

non-condensing

Beeper

Yes

Index of Protection

KR600-E/M: IP65

KR601-E/M: IP65

KR602-E/M: IP64

Dimensions

	KR600 E/M	KR601 E/M	KR602 E/M
Height:	11.6cm	8.6cm	8.6cm
Depth:	1.6cm	1.6cm	2cm
Width:	7.5cm	8.6cm	8.6cm



ZKTeco Biometrics India Pvt. Ltd.
www.zkteco.in
 E-mail: sales@zkteco.in

© Copyright 2020. ZKTECO CO., LTD. ZKTeco Logo is a registered trademark of ZKTeco or a related company. All other product and company names mentioned are used for identification purposes only and may be the trademarks of their respective owners. All specifications are subject to change without notice. All rights reserved.

