

TS2122 Tripod Turnstile with Controller and Fingerprint & RFID Reader

The TS2122 offer a slim, two-legged casework made of stainless steel, ideal for sites where a high traffic and space are issued. It is suitable for areas with a high traffic.

By receiving a signal from the access control system, or pushing button, it allows the entry of one person in a time. The status is shown on the led-way mode indicators on the top. Entering into different directions are electronically controlled. Default mode is to lock the mechanism until a valid authorization signal is received. If you want to set one side free, you can have it by adjusting the mechanism. In case of emergency, the horizontal arm will drop to allow free passage. Led way mode indicators are included as standard.

TS2122



SPECIFICATION

Power Supply	AC 220V/110V, 50/60Hz
Operating Temperature	-28°C- 60°C
Operating Humidity	5%-85%
Working Environment	Indoor/Outdoor(shelter)
Rated Power	60W
Flow Rate	25- 48 passage/minute
Casework Material	SUS304
Pictogram Indication	Yes
Control System	Input controlled by dry contact
Emergency Button Input	Yes
Dimension	111×98×18(CM) + arm length 50CM
Package Dimension	120×108×28(CM)
Net Weight	45KG
Gross Weight with Package	53KG
Optional Function	Alternative material or shape, third-party access control integration, ticket system integration, passage counter

FEATURES

Reliability

- *Alloy steel tripod hub prevents mechanical wear*
- *Casework and tripod arms manufactured in SUS304 stainless steel*
- *Electromagnets for lock are used only when being activated. They are in standby mode when the device is idle.*
- *High quality electrical components*

Safety and User-Orientated Design

- *Drop arm designed for emergency purpose*
- *No exposed screws, safer for the user.*
- *Smooth operation designed for mass transit application*
- *The pictogram on the device indicating access permission and direction of movement*
- *Special designed case shape, user-friendly for passenger to punch card or finger.*
- *Anti-tailgate*

Easy Integration

- *Flexible reader installation plate. Customers can easily integrate with third party reader*
- *Standard electrical interface for third party device.*
- *Using compact mechanism, the turnstile has more space inside for integration*
- *The design of being vacuum at the bottom part of the device, enables easy installation for other hardware.*